Insulated Multi-Color Skirting

TrimLock_{Ltd}

Home Base Skirting Protection at its Best



RTM Homes

Modular Homes

New & Remodeling

Open Base Foundations

Solid Foundations & Para

Our hard shell panel is a result of 32 years of proven performance for above grade exterior protection. The unique finish offers multiple colors, impact resistant, excellent performance against harsh weather conditions.







Ph (250) 861-6795 Fx (250) 861-679 www.canadianvinyls.com

Auto Vent inserts

TrimLock_{Ltd}

Home Base Skirting Protection at its Best



RTM Homes
Modular Homes
New & Remodeling
Open Base Foundations
Solid Foundations & Parg

Auto Vent inserts

Our hard shell panel is a result of 32 years of proven performance for above grade exterior protection. The unique finish offers multiple colors, impact resistant, excellent performance against harsh weather conditions.

www.canadianvinyls.com





Product Data

Exterior Skirting Panels (Manufactured Homes)

Description

TrimLock Skirting Panel is a uniquely produced light weight Panel, 38.1 (1 ½") thick x 1219.2 mm (48") wide x 3657.6mm (144") long Acrylic stucco hard shell protection, reinforced edge and supporting metal trim.

Each panel is specifically designed using a proprietary procedure for producing enhanced strength and flexibility Acrylic stucco insulating system, provides superior stability, strength, resistance to every day weather environments, raw materials used are of the highest quality available in the marketplace and meet or exceed CAN/ULC / ASTM / CGSB testing results.

Performance codes & Classifications

CCMC- 13103-R
CGSB- 1GP-162M
CAN/ULC- S701-97
CAN/UCL- S102-M83
Flame spread 8
Smoke develop less than 5
Fuel Contribution less than 5
EIMA-101-86 impact resistance
-3 joules (.0302 kgf-m) passed

- -3 joules (.0302 kgf-m) passed no cracks
- -10 joules (1.02 kgf-m) passed no Perforation

ASTM- E283-91/ D897/ D579/ D568/ D822-9

Applications

- -Manufactured Homes
- -New Residential & Commercial
- -Renovations
- -Projects requiring added insulation
- -Complete wall parging cladding
- -Open skirting
- -Wood surfaces
- -Concrete surfaces
- -Masonry surfaces
- -ICF block

Features

- -Insulated Panel with (RSI 0.99) or (R5.6)
- -Floating panels for ground and home movement
- -Light weight for easy handling
- -Multiple color/ True colour system
- -Maintenance free
- -European acrylic stucco finish
- -Environmentally friendly

Benefits

- -EPS insulated Panels factory finished ready to install
- -Repels water /wind /heat /cold
- -No expansion and contraction due to heat and cold
- -Impact resistance
- -Flexible
- -Commercial Grade Acrylic Stucco system
- -Multiple colors
- -Fire retardant acrylic finish & EPS foam insulation
- -Each panel has its own fastening edge flange
- -Compatible with walls/Glues to concrete brick/ ICF block
- -Can be used as parging panel for concrete basements -Cut with masonry blade /skill saw / mitre saw/ utility knife
- -Lower cost compared to onsite stucco applications
- -Light weight for easy handling and less wall stress
- -Detailed appearance of First Class Quality
- -Excellent performance with noise reduction
- -Exceptional performance in wind driven environments
- -Reduces energy cost, summer and winter

Qualities & Strength:

TrimLock skirting panel offers the strength and quality of a high performance commercial grade, Exterior Insulating Finishing System (EIFS) with thermal insulating characteristics. Only the finest quality, time tested and industry proven raw materials make up the Trimlock skirting/parging panel for quality assurance.



#4 – 1610 Innovation Dr Kelowna BC V1W 3Z6 250.861.6795 Fax 250.861.6791

Product Data



Exterior Skirting Panels (Manufactured Homes)

Description

TrimLock Skirting Panel is a uniquely produced light weight Panel, $38.1 (1 \frac{1}{2})$ thick x 1219.2 mm (48") wide x 3657.6mm (144") long Acrylic stucco hard shell protection, reinforced edge and supporting metal trim.

Features

- -Insulated Panel with (RSI 0.99) or (R5.6)
- -Floating panels for ground and home movement
- -Light weight for easy handling
- -Multiple color/ True colour system
- -Maintenance free
- -European acrylic stucco finish
- -Environmentally friendly

Each panel is specifically designed using a proprietary procedure for producing enhanced strength and flexibility Acrylic stucco insulating system, provides superior stability, strength, resistance to every day weather environments, raw materials used are of the highest quality available in the marketplace and meet or exceed CAN/ULC / ASTM / CGSB testing results.

Performance codes & Classifications

CCMC- 13103-R CGSB- 1GP-162M CAN/ULC- S701-97

CAN/UCL- S102-M83

Flame spread 8

Smoke develop less than 5 Fuel Contribution less than 5

EIMA-101-86 impact resistance

- -3 joules (.0302 kgf-m) passed no cracks
- -10 joules (1.02 kgf-m) passed no Perforation

ASTM- E283-91/ D897/ D579/ D568/ D822-9

Applications

- -Manufactured Homes
- -New Residential & Commercial
- -Renovations
- -Projects requiring added insulation
- -Complete wall parging cladding
- -Open skirting
- -Wood surfaces
- -Concrete surfaces
- -Masonry surfaces
- -ICF block

Benefits

- -EPS insulated Panels factory finished ready to install
- -Repels water /wind /heat /cold
- -No expansion and contraction due to heat and cold
- -Impact resistance
- -Flexible
- -Commercial Grade Acrylic Stucco system
- -Multiple colors
- -Fire retardant acrylic finish & EPS foam insulation
- -Each panel has its own fastening edge flange
- -Compatible with walls/Glues to concrete brick/ ICF
- -Can be used as a parging panel for concrete basements -Cut with masonry blade /skill saw / mitre saw / utility
- knife
 -Lower cost compared to onsite stucco applications
- -Light weight for easy handling and less wall stress
- -Detailed appearance of First Class Quality
- -Excellent performance with noise reduction
- -Exceptional performance in wind driven environments
- -Reduces energy cost, summer and winter

Qualities & Strength:

TrimLock skirting panel offers the strength and quality of a high performance commercial grade, Exterior Insulating Finishing System (EIFS) with thermal insulating characteristics. Only the finest quality, time tested and industry proven raw materials make up the TrimLock skirting/parging panel for quality assurance



#4 – 1610 Innovation Dr Kelowna BC V1W 3Z6